CROCODILE
ECOSHIELD

CROCODILE



Waterproofing with One Component

For Pre-Tiling Work



CROCODILE ECOSHIELD

Waterproofing Cement Coating – 1K

- Easy to use, just mix with water
- No smell and non-toxic
- Highly adhesive for wall and floors before tiling
- Very cost-effective, with up to 15 sq.m. coverage
- Easy and fast application
- Protect against water penetration
- Can apply by brush or trowel

- For restrooms, balconies, floors, and walls before tiling -

CROCODILE **ECOSHIELD**

Waterproofing Cement Coating – 1K

"Waterproofing with one component for pre-tiling work"









Usage Area


Crocodile Ecoshield is a waterproofing cement coating with one component. It is easy to use by just mixing with water, help reducing the error of mixing two components like other traditional waterproofing.
No smell, and able to cover the cracks on the surface. High adhesion and can apply by brush or trowel on the concrete or plaster to waterproof and protect building structures from water leak. Very cost-effective, with up to 15 sq.m. coverage per two applications.

Application Instruction

Substrate Preparation

- Clean the surface to be free from dust, grease, concrete scrap, or unknown matter etc.
- Fill cracks if any on the surface with suitable repairing material. Fill wall border or joints with sealant.
- The concrete surface must be damp.

Application




Apply on the surface with brush or roller twice.



The second coat should be applied in perpendicular of the first coat, allowing 30-90 minutes apart between each application.



The surface should be left to dry at least 3 days.



Tile work should be done on surface after 3 days.

Estimated Coverage

- 1-1.5 kg / sq.m./ 2 coats

Packing

- 20 kg (bag)

Product Information

+66 (0) 2720 1112 JorakayPage www.jorakay.co.th
10 Krungthepkreetha Road, Tab Chang Subdistrict, Sapan Sung District, Bangkok,10250, Thailand

U.S.A. Standard from the Crocodile Family

Jorakay Corporation Co., Ltd.