CROCODILE

ROOF SHIELD

CROCODILE



The One & Only

Waterproofing

Heat Proofing

5 - Time Elongation!



CROCODILE ROOF SHIELD

Acrylic Waterproofing

- Ready to use
- Powerful waterproofing
- Cover cracks
- Reflects heat and reduce temperature by 2 - 6 degrees
- Highly flexible, up to 500% elongation
- Adheres to almost all surfaces

- For waterproofing for roof, wall and rooftop -

CROCODILE ROOF SHIELD

Acrylic Waterproofing

"The one & only waterproofing, heat proofing, 5-time elongation!"







Usage Area


Crocodile Roof Shield is instant acrylic waterproofing for roof, wall, or rooftop. When dried, the shield will look like a thin rubber sheet that prevent seeping. It is highly flexible with special ingredient that come with total solar reflectiveness between 55-80%, reducing heat inside the building and resulting in better cooling than normal acrylic by 2-6 degrees. Suitable for sloped surface, or wide area with good drainage, or joints and small hairline cracks (less than 1.5 mm)

Application Instruction

Substrate Preparation

- Clean the surface to be free from dust, grease, concrete scrap, or unknown matter etc.
- Fill cracks if any on the surface with suitable repairing material. Fill wall border or joints with sealant.
- Leave the surface dry at least 3 hours after cleaning.
- New concrete wall or floor should be at least 28 days old before applying waterproofing.
- New plastered surface should be at least 7 days old before applying waterproofing.
- Moisture-retaining material should be completely dry before applying waterproofing.


Application




Stir it before use (When used as a primer, dilute the mixture with 5-10% water and apply.)



Apply it twice by using a brush or roller (Allow the first coat to dry for 4 hours, then apply the second coat)



If fiber mesh is needed, put up the fiber mesh after the first coats application while it is still not dry. It is recommended to apply the second coat to fully cover the mesh.



When finished, surface should be left to dry at least 48 hours.

Estimated Coverage

- 1.2 kg / sq.m. / 2 coats (0.2-0.4 mm thickness)
- As primer: approx. 0.6 kg / sq.m. (dilute 10% of water)

Packing

- 1 kg (bucket)
- 4 kg (bucket)
- 20 kg (bucket)

Color

- White / Grey

Product Information

+66 (0) 2720 1112 JorakayPage www.jorakay.co.th

10 Krungthepkreetha Road, Tab Chang Subdistrict, Sapan Sung District, Bangkok,10250, Thailand

U.S.A. Standard from the Crocodile Family

Jorakay Corporation Co., Ltd.