CROCODILE

ACRYLIC SEALANT GATOR

CROCODILE

Wall Joint Sealing Paintable

Seal the Joint

Fast-Drying



CROCODILE SEALANT GATOR

Ready - to - Use Latex - Base Sealant

- Flexible
- For sealing the wall joint, crack or fracture
- Fast setting & paintable
- High adhesion

- For wood, concrete, ceramic, tiles, brick, plastered wall, synthetic wood –

CROCODILE

ACRYLIC SEALANT GATOR

Ready - to - Use Latex - Base Sealant

"Instant general - purpose acrylic sealant"













Usage Area

Crocodile Acrylic Sealant Gator is a one - component, ready to use latex-base sealant, with good adhesion performance on various kinds of substrates such as wood, concrete, ceramic, tiles, brick, plastered wall, synthetic wood, etc. It is odor free and not corrosive towards metals.

Application Instruction

Substrate Preparation

- The substrate must be clean, dry, dust-free and without any traces of oil, laitance, curing compound etc.
- Joint sizes may range from 3 - 12 mm in width and 5 - 10 mm in depth. The width should be wider but smaller than the depth, for better elongation. Bond breaker may be used to adjust the depth/width ratio.


Application



Cut off the nozzle tip at 45 - degree angle and position the cartridge in a manual or air powered caulking gun.




Tape up both sides of the joint to prevent overfilling.



Squeeze out to fill the joint.



Wipe off the excess sealant with wet rag or sponge.



Remove the masking tapes within 10 - 15 minutes before it cures.



Leave it for 24 hours before use or painting.

Estimated Coverage

- 3 meters per cartridge (for 1x1 cm joint width)

Packing

- 450 grams

Product Information

+66 (0) 2720 1112 JorakayPage www.jorakay.co.th

10 Krungthepkreetha Road, Tab Chang Subdistrict, Sapan Sung District, Bangkok,10250, Thailand

U.S.A. Standard from the Crocodile Family

Jorakay Corporation Co., Ltd.